



Image for illustrative purpose only

Summary

Request a quote

Catalog

| Jacket cable outside diameter [mm] | 7.00 - 7.70 mm |
|------------------------------------|------------------|
| Size | 2B |
| Series | B - Indoor keyed |


https://www.lemo.com/int_en/solutions/originals/b-indoor-keyed/gma-2b-070-dn.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Technical details

| Form & Material | | |
|------------------------------------|--|--|
| Shell style / Model id | GMA - Bend relief Black | |
| Housing material | Thermoplastic polyurethane | |
| Keying | No keying | |
| Colour | Black | |
| Weight | 1.84 g | |
| Environment | | |
| Technical domain | Audio Video, Energy and Industrial, Medical, Semiconductor, Specialties and Other, Test and Measurement, Transportation, Aerospace and UAV | |
| Environmental sealing (IP rating) | No IP rating | |
| Temperature range | -40°C / +80°C | |
| Cable fixation | | |
| Jacket cable outside diameter [mm] | 7.00 - 7.70 mm | |

Drawings



No keying

Dimensions

| | Α | L |
|-----|------|------|
| mm. | 7.0 | 36 |
| in. | 0.28 | 1.42 |

https://www.lemo.com/int_en/solutions/originals/b-indoor-keyed/gma-2b-070-dn.html

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.