



280 Clinton St. Springfield, VT 05156  
Phone (866) 403-5223 Fax (802) 885-6210  
[www.imageteklabels.com](http://www.imageteklabels.com)

## **LMA3006**

### **White Semi-Gloss Paper**

**Description** - 3.2 Mil white, semi-gloss premium digital paper stock with a cold temp emulsion acrylic adhesive. Features excellent ink anchorage and high strength for die-cutting and matrix stripping.

**Use** - This label is a general low-cost label ideal for shipping and product labeling.

#### **Material Specification:**

|   |         |                           |                |
|---|---------|---------------------------|----------------|
| <b>Substrate:</b>   | Paper   | <b>Thickness of Mat'l</b> |                |
|   |         | Film                      | 3.2 Mil        |
| <b>Color:</b>   | White   | Adhesive                  | 0.5 Mil        |
|   |         | Liner                     | 2.5 Mil        |
| <b>Topcoat:</b>   | Digital | <b>Total</b>              | <b>6.2 Mil</b> |
| <b>Minimum Application Temp:</b> + 25°F (4°C)                   |         |                           |                |
| <b>Working Temperature Range:</b> -10°F to 200°F (23°C to 93°C) |         |                           |                |
| <b>Liner:</b> 40# bleached kraft                                |         |                           |                |

#### **Adhesive Specifications:**

**Type:** Emulsion Cold Temp Acrylic

**Characteristics:** Permanent

**Surfaces:** Large range of applications including rough or textured surfaces, corrugated, plastic packing materials and more

#### **Recommended Ribbons:**

**Shelf Life:** 1 year at 70°F (21°C) and 50% R.H.

*Technical specifications are provided for general information only and should not be relied upon for designs and specifications, or be relied on as meeting specified performance criteria. As with all pressure-sensitive materials, this product should be tested thoroughly under end-use conditions to make*