



280 Clinton St. Springfield, VT 05156
Phone (802) 885-6208 Fax (802) 885-6210
www.imageteklabels.com

LMP6000

Gloss White Polyester

Description - 2 Mil gloss, white polyester with permanent adhesive for thermal transfer printing. UL recognized and CSA accepted. RoHS compliant.

Use - This label is general purpose polyester with excellent smear, scratch and chemical resistance. Also used for top side labeling in PCB applications, property ID, warning instruction and service labels for durable goods. Use on painted metals, glass, high energy plastics and metals, acrylics, fiberglass, stainless steel and PCB's.

Material Specification:

Substrate:	2 Mil Polyester Film	Thickness of Mat'l	
		Film	2.0 Mil
Color:	Gloss, White	Adhesive	0.8 Mil
		Liner	3.2 Mil
Topcoat:	Thermal Transfer Printable	Total	6.0 Mil
Working Temperature Range: -40°F to 300°F (-40°C to 149°C)			
Liner: 55# Densified Kraft Paper			

Adhesive Specifications:

Type: Acrylic

Characteristics: Permanent

Application Temperature: 50°F (10°C)

Recommended Ribbons:

LMW2100 Series

Shelf Life: 24 months at 72°F (22°C) and 50% R.H.

Technical specifications are provided for general information only and should not be relied upon for designs and specifications, or be relied on as meeting specified performance criteria. As with all pressure-sensitive materials, this product should be tested thoroughly under end-use conditions to make sure it meets the requirements of the specific application.